



Smart solutions for a **sustainable** world

60kW CHARGER



» **High efficiency**

- A battery charger with two outputs that charge simultaneously
- Two CCS2 DC connectors with output up to 60 kW
- Constant power from 300 to 1000 voltage, less heat with lower current

» **Flexible option**

Operation by App/RFID Authentication/Plug&Play
High protection rating of IP54

» **Smart**

- Ethernet and Wi-Fi communication supported, 4G optional
- Smart control via App

» **Safe and secure**

- Type-A RCD for residual current protection
- MID-certified AC meter
- ISO 15118 prepared for advanced Plug & Play operation



60kW

EV-CHARGER



Technical data	ZVD-60K-POWER/P ZVD-60K-POWER/D
AC Input data	
Type of connection	Three-phase (3PH + Neutral + PE)
AC input voltage	400V +/- 10%
Rated AC input current	96A
AC input frequency	50/60Hz
Power factor	>0.99% (from 50% to 100% power)
THD	<5% (at 100% power)
DC Output data	
DC output voltage	200-500V (CHAdeMo) 200-1000V (CCS2)
Maximum DC output current	125A (CHAdeMo) 200A (CCS2)
Maximum power	60kW
General data	
Charging connectors	1x CHAdeMO, 1x CCS2 (ZVD-60k-POWER-D) 2x CCS2 (ZVD-60k-POWER-P)
Cable length	5m
Installation	On concrete platform
LCD screen	LCD touch-screen display 10.1"
Charging start	RFID Card, APP, Plug-In
Energy Meter	MID certified
RCD protection	TypeA + 6mA DC
Protection rating	IP54 (ambient) IK07 (impact)
Cooling	Internal fans on modules
Emergency stop	Yes
Communication	Wi-Fi, Ethernet
Protocol	OCPP 1.6 JSON (possible upgrade to JSON 2.0)
Maximum conversion efficiency	95%
Environmental Data	
Operating temperature	-30°C / +50°C
Humidity	5% / 95% non-condensing
Maximum altitude	2000mt
Installation	Indoor / Outdoor
Safety protections	
Integrated protections	under voltage, power overload, short circuit, dispersion currents, missing ground connection, surge, over and under temperature
Applicable safety standards	IEC 61851-1: 2019, EN 61851-23:2014, EN 61851-24:2014
Warranty	2 years
Dimensions and accessory parts	
Dimensions (H x L x D)	1830mm x 750mm x 525mm
Dimensions of wooden crate (H x W x D)	2020mm x 1020mm x 750mm
Weight	228 kg
Weight including wooden crate	268,5 kg



zcsazzurro.com

1st ED. 2024-01

Zucchetti Centro Sistemi S.p.A.
Green Innovation Division
Palazzo dell'Innovazione - Via Lungarno, 167
52028 Terranuova Bracciolini - Arezzo, Italy
tel. +39 055 - 91971 - fax. +39 055 - 9197515
innovation@zcscompany.com - zcscompany.com

ZCS AZZURRO

 **ZUCCHETTI**
Centro Sistemi 