

Certificate of Conformity

Certificate Number: CN-PV-210240

manufacturing process assures certificate.	compliance of the production units with the examined products mentioned in this
Applicant Name & Address:	Zucchetti Centro Sistemi SpA
	Via Lungarno 305/A 52028 Terranuova Bracciolini (AR) Italy
Product Description:	Solar Grid-tied Inverter
atings & Principle	See Annex to Certificate of Conformity
Characteristics:	
Models/Type References:	AZZURRO 3PH 3.3KTL-V3, AZZURRO 3PH 4.4KTL-V3,
	AZZURRO 3PH 5.5KTL-V3, AZZURRO 3PH 6.6KTL-V3
	AZZURRO 3PH 8.8KTL-V3, AZZURRO 3PH 11KTL-V3
	AZZURRO 3PH 12KTL-V3, AZZURRO 3PH 5KTL-V3-A
	AZZURRO 3PH 8.8KTL-V3-A, AZZURRO 3PH 10KTL-V3-A
	AZZURRO 3PH 11KTL-V3-A
Brand Name:	{ ZCS
Specification/Standard:	RD1699:2011
	UNE 206006 IN:2011
	UNE 206007-1 IN:2013
	Regulating the connection to the electrical grid of small-scale power
	generation facilities.
Certificate Issuing Office Name	Intertek Testing Services Ltd. Shanghai
Address:	West Area, 2nd Floor, No. 707, Zhangyang Road China (Shanghai) Pilot Free
a Address.	Trade Zone, Shanghai, P. R. China
	Accredited by China National Accreditation Service for Conformity
	Accredited by clinia National Accreditation Service for Comonity Assessment (CNAS C058-P) in accordance with ISO/IEC 17065:2012
est Report Number:	210727048GZU-013
est Report Number. ertification procedure: SMS-PV	
oduct certification scheme typ	
dditional information in Appen	

/mayle

Signature

Certification Manager: Grady Ye Date: 21 Oct. 2021





APPENDIX: Certificate of Conformity

This is an Appendix to Certificate of Conformity Number: CN-PV-210240

	1	1		1
MODEL	AZZURRO 3PH 3.3KTL-V3	AZZURRO 3PH 4.4KTL-V3	AZZURRO 3PH 5KTL-V3-A	AZZURRO 3PH 5.5KTL-V3
Max PV voltage	1100Vdc			
MPPT Voltage range	140-1000Vdc			
Max. input current	15/15A			
PV lsc	22.5/22.5A			
Rated power(W)	3000	4000	5000	5000
Max.apparent power (VA)	3300	4400	5000	5500
Max output current	3×5.0 A	3×6.7 A	3×7.6 A	3×8.3 A
Output voltage	3W/N/PE 230Vac/400Vac			
Nominal Frequency	50 Hz			
Power Factor	1 default (adjustable+/-0.8)			
Ambient Temperature	- 30 ℃ - +60℃			
Protection Degree	IP65			
Protection Class	Class I			
Software Version	V000001			



APPENDIX: Certificate of Conformity

This is an Appendix to Certificate of Conformity Number: CN-PV-210240

MODEL	AZZURRO 3PH 6.6KTL-V3	AZZURRO 3PH 8.8KTL-V3	AZZURRO 3PH 8.8KTL-V3-A	AZZURRO 3PH 10KTL-V3-A
Max PV voltage	1100Vdc			
MPPT Voltage range	140-1000Vdc			
Max. input current	15/15A 15/30A			30A
PV lsc	22.5/22.5A		22.5A/45A	
Rated power(W)	6000	8000	8000	10000
Max.apparent power (VA)	6600	8800	8800	10000
Max output current	3×10.0 A	3×13.3 A	3×13.3 A	3×15.2 A
Output voltage	3W/N/PE 230Vac/400Vac			
Nominal Frequency	50 Hz			
Power Factor	1 default (adjustable+/-0.8)			
Ambient Temperature	-30℃ - +60℃			
Protection Degree	IP65			
Protection Class	Class I			
Software Version	V000001			



APPENDIX: Certificate of Conformity

This is an Appendix to Certificate of Conformity Number: CN-PV-210240

MODEL	AZZURRO 3PH 11KTL-V3	AZZURRO 3PH 11KTL- V3-A	AZZURRO 3PH 12KTL- V3	
Max PV voltage	1100Vdc			
MPPT Voltage range	140-1000Vdc			
Max. input current	15A/15A 15A/30A			
PV lsc	22.5/22.5A 22.5A/45A			
Rated power(W)	10000	10000	12000	
Max.apparent power (VA)	11000	11000	13200	
Max output current	3×16.7 A	3×16.7 A	3×20.0 A	
Output voltage	3W/N/PE 230Vac/400Vac			
Nominal Frequency	50 Hz			
Power Factor	1 default (adjustable+/-0.8)			
Ambient Temperature	-30℃ - +60℃			
Protection Degree	IP65			
Protection Class	Class I			
Software Version	V000001			