

Certificate of Conformity

Certificate Number: CN-PV-210242

requirements of the referenced Intertek has performed any sur	caken, the samples of the below product have been found to comply with the I specifications /standards at the time the tests were carried out. It does not imply that veillance or control of the manufacture. The manufacturer shall ensure that the compliance of the production units with the examined products mentioned in this			
Applicant Name & Address:	Zucchetti Centro Sistemi SpA			
	Via Lungarno 305/A 52028 Terranuova Bracciolini (AR) Italy			
Product Description:	Anti-backflow system			
Ratings & Principle	See Annex to Certificate of Conformity			
Characteristics:				
Models/Type References:	AZZURRO 3PH 3.3KTL-V3, AZZURRO 3PH 4.4KTL-V3,			
	AZZURRO 3PH 5.5KTL-V3, AZZURRO 3PH 6.6KTL-V3			
	AZZURRO 3PH 8.8KTL-V3, AZZURRO 3PH 11KTL-V3			
	AZZURRO 3PH 12KTL-V3, AZZURRO 3PH 5KTL-V3-A			
	AZZURRO 3PH 8.8KTL-V3-A, AZZURRO 3PH 10KTL-V3-A			
	AZZURRO 3PH 11KTL-V3-A			
Brand Name:	7263			
Specification/Standard:	UNE 217001 IN: October 2020			
	Tests for systems that avoid the discharge of energy to the distribution network			
Certificate Issuing Office Name	Intertek Testing Services Ltd. Shanghai			
& Address:	West Area, 2nd Floor, No. 707, Zhangyang Road China (Shanghai) Pilot Free			
	Trade Zone, Shanghai, P. R. China			
	Accredited by China National Accreditation Service for Conformity			
	Assessment (CNAS C058-P) in accordance with ISO/IEC 17065:2012			
Test Report Number:	210727048GZU-015			
Certification procedure: SMS-PV				
Product certification scheme typ				
Additional information in Appen	dix.			
Consta	uBER OF MULTILATE. 中国认可			

Signature

Certification Manager: Grady Ye Date: 02 November 2021





APPENDIX: Certificate of Conformity

This is an Appendix to Certificate of Conformity Number: CN-PV-210242

MODEL	AZZURRO 3PH 3.3KTL-V3	AZZURRO 3PH 4.4KTL-V3	AZZURRO 3PH 5KTL-V3-A	AZZURRO 3PH 5.5KTL-V3
Max PV voltage	1100Vdc			
MPPT Voltage range	140-1000Vdc			
Max. input current	15/15A			
PV lsc	22.5/22.5A			
Rated power(W)	3000	4000	5000	5000
Max.apparent power (VA)	3300	4400	5000	5500
Max output current	3×5.0 A	3×6.7 A	3×7.6 A	3×8.3 A
Output voltage	3W/N/PE 230Vac/400Vac			
Nominal Frequency	50 Hz			
Power Factor	1 default (adjustable+/-0.8)			
Ambient Temperature	- 30 ℃ - +60℃			
Protection Degree	IP65			
Protection Class	Class I			
Software Version	V000001			



APPENDIX: Certificate of Conformity

This is an Appendix to Certificate of Conformity Number: CN-PV-210242

MODEL	AZZURRO 3PH 6.6KTL-V3	AZZURRO 3PH 8.8KTL-V3	AZZURRO 3PH 8.8KTL-V3-A	AZZURRO 3PH 10KTL-V3-A	
Max PV voltage	1100Vdc				
MPPT Voltage range	140-1000Vdc				
Max. input current	15/15A 15/30A			30A	
PV lsc	22.5/22.5A		22.5A/45A		
Rated power(W)	6000	8000	8000	10000	
Max.apparent power (VA)	6600	8800	8800	10000	
Max output current	3×10.0 A	3×13.3 A	3×13.3 A	3×15.2 A	
Output voltage	3W/N/PE 230Vac/400Vac				
Nominal Frequency	50 Hz				
Power Factor	1 default (adjustable+/-0.8)				
Ambient Temperature	-30°C - +60°C				
Protection Degree	IP65				
Protection Class	Class I				
Software Version	V000001				



APPENDIX: Certificate of Conformity

This is an Appendix to Certificate of Conformity Number: CN-PV-210242

MODEL	AZZURRO 3PH 11KTL-V3	AZZURRO 3PH 11KTL- V3-A	AZZURRO 3PH 12KTL- V3	
Max PV voltage	1100Vdc			
MPPT Voltage range	140-1000Vdc			
Max. input current	15A/15A 15A/30A			
PV lsc	22.5/22.5A 22.5A/45A			
Rated power(W)	10000	10000	12000	
Max.apparent power (VA)	11000	11000	13200	
Max output current	3×16.7 A	3×16.7 A	3×20.0 A	
Output voltage	3W/N/PE 230Vac/400Vac			
Nominal Frequency	50 Hz			
Power Factor	1 default (adjustable+/-0.8)			
Ambient Temperature	- 30 ℃ - +60℃			
Protection Degree	IP65			
Protection Class	Class I			
Software Version	V000001			