

Certificate of Conformity

Certificate Number: CN-PV-230626

On the basis of the tests undertaken, the sample<s> of the below product have been found to comply with the requirements of the referenced specification<s>/standard<s> at the time the tests were carried out. It does not imply that Intertek has performed any surveillance or control of the manufacture(s). The manufacturer(s) shall ensure that the manufacturing process assures compliance of the production units with the examined products mentioned in this certificate.

Applicant: Zucchetti Centro Sistemi SpA

Via Lungarno 305/A 52028 Terranuova Bracciolini (AR) Italy

Product: Solar Grid-tied Inverter

Ratings & Principle See appendix of Certificate of Conformity

Characteristics:

Model: AZZURRO 3PH 25KTL-V3, AZZURRO 3PH 30KTL-V3, AZZURRO 3PH 30KTL-V3-A,

AZZURRO 3PH 33KTL-V3, AZZURRO 3PH 36KTL-V3, AZZURRO 3PH 40KTL-V3, AZZURRO 3PH 45KTL-V3, AZZURRO 3PH 50KTL-V3, AZZURRO 3PH 40KTL-V3-

HV, AZZURRO 3PH 50KTL-V3-HV

Brand Name<s>:

Product Complies with: UTE C 15-712-1:2013

DIN V VDE V 0126-1-1:2013 Enedis-PRO-RES_10E version 5

Certificate Issuing Office Intertek Testing Services Ltd. Shanghai

Name & Address: West Area, 2nd Floor, No. 707, Zhangyang Road

China (Shanghai) Pilot Free Trade Zone, Shanghai, P. R. China

Accredited by ACCREDIA in accordance with ISO/IEC 17065:2012

Test Report No.<s>: 231103040GZU-001, 14 November 2023

231103040GZU-002, 14 November 2023

Additional information in Appendix.

Signature

Certification Manager: Grady Ye

Cousta

Date: 20 November 2023

ACCREDIA T

PRD N° 306B



APPENDIX: Certificate of Conformity

This is an Appendix to Certificate of Conformity Number: CN-PV-230626.

Model	AZZURRO 3PH 25KTL-V3	AZZURRO 3PH 30KTL-V3	AZZURRO 3PH 30KTL- V3-A			
Max. DC input Voltage	1100Vdc					
Operating MPPT voltage range	180Vdc — 1000Vdc					
Max. Input current	40A*3					
PV Isc	50A*3					
Nominal AC output voltage	3/N/PE 230Vac/400Vac					
Nominal AC output Frequency						
Max. AC output current	42.4A	51.5A	45.3A			
Nominal Output power	25000W	30000W	29900W			
Max.Output Power	28000VA	34000VA	29900VA			
Power factor	1(adjustable +/-0.8)					
Safety level	Class I					
Ingress Protection	IP 65					
Operation Ambient Temperature	-30℃ - 60℃					
Software version	V000001					



APPENDIX: Certificate of Conformity

This is an Appendix to Certificate of Conformity Number: CN-PV-230626.

Model	AZZURRO 3PH 33KTL-V3	AZZURRO 3PH 36KTL-V3	AZZURRO 3PH 40KTL- V3			
Max. DC input Voltage	1100Vdc					
Operating MPPT voltage range	180Vdc – 1000Vdc					
Max. Input current	40A*	40A*4				
PV Isc	50A*	50A*4				
Nominal AC output voltage	3/N/PE 230Vac/400Vac					
Nominal AC output Frequency	50Hz					
Max. AC output current	56A	60.6A	66.7A			
Nominal Output power	33000W	36000W	40000W			
Max.Output Power	37000VA	40000VA	44000VA			
Power factor	1(adjustable +/-0.8)					
Safety level	Class I					
Ingress Protection	IP 65					
Operation Ambient Temperature	-30℃ - 60℃					
Software version	V000001					



APPENDIX: Certificate of Conformity

This is an Appendix to Certificate of Conformity Number: CN-PV-230626.

Model	AZZURRO 3PH 45KTL-V3	AZZURRO 3PH 50KTL-V3	AZZURRO 3PH 40KTL-V3-HV	AZZURRO 3PH 50KTL-V3-HV		
Max. DC input Voltage	1100Vdc					
Operating MPPT voltage range	180Vdc – 1000Vdc					
Max. Input current	40A*4		40A*3	40A*4		
PV Isc	50.	50A*4		50A*4		
Nominal AC output voltage	3/N/PE 230Vac/400Vac		3/N/PE 277Vac/480Vac			
Nominal AC output Frequency	50Hz					
Max. AC output current	75.8A	83.3A	53.0A	66.2A		
Nominal Output power	45000W	50000W	40000W	50000W		
Max.Output Power	50000VA	55000VA	44000VA	55000VA		
Power factor	1(adjustable +/-0.8)					
Safety level	Class I					
Ingress Protection	IP 65					
Operation Ambient Temperature	-30℃ - 60℃					
Software version	V000001					